



# BARINDER<sup>F</sup> 400 Series



## X6i-FDH22R-443GR

Automatic deburring machine for small and medium sized castings.



### Features

- Best deburring machine for small and medium sized castings.
- Rotating main & auxiliary tool- head.
- Suitable for the finishing complex shape castings.
- Main tool-head now powered by servo-motor for improved efficiency.

### Outline of specifications

Max. machinable size	Φ400×H200, 20kg (*Load capacity is within 30kg)
Main tool-head	Diamond wheel Φ355×T12×Φ80
Main tool-head driving motor	4.5Kw (AC servomotor drive)
Auxiliary tool-head driving motor	2.2Kw (High speed type, Inverter drive)
Wheel tilt for max.	130° (NC control drive)
Control driving motor,	6 axes AC servo controlled by NACR
Number of NC axis	
Overall dimensions	W1700×D2185×H2081
Weight	1750kg

\*Load capacity includes casting, fixture, and fixture palette.

## Challenging to Future Function of BARINDER!!

# X6i-FDH22R-443GR

### ■ Grinding by tilting main shaft tool



(Appeared object is virtual image)

### ■ Features

- 1.Small footprint.
- 2.One operator can perform multiple machine operations.
- 3.Program creation is simple and easy.
- 4.Simple operation with high function.
- 5.Quick change- less than 5 min. to change fixtures, programs and tools.
- 6.Diamond tool saves operation cost and dust generation.
- 7.High speed and efficient processing enables productivity and a higher finishing quality of product.

### ■ Object example Subject material : FC, FCV, FCD, BC-6, ADC, others



**Exhaust Manifold**  
30 sec / piece



**Differential Case**  
24 sec / piece



**Differential Carrier**  
24 sec / piece



**Rotor**  
40 sec / piece




**Gear Box**  
24 sec / piece



**Axle case**  
40 sec / piece



**Water Pump**  
37 sec / piece



**Cylinder Head**  
27 sec / piece

\*The grinding tact times are for reference only, not guaranteed values.

Inquiry

**KOYAMA CO., LTD.**

**Suzaka Factory Development Department**

3500-1, Mushiokuri, Hitaki, Suzaka-City, Nagano-Pref.,  
382-0011 Japan.

TEL +81-26-215-2811 FAX +81-26-215-2812

<http://www.barinder.jp>

CNo. X6i-FDH22R-443GR-E